



Henan Huaxing Wires and Cable Co.,Ltd
 Yong'an Industry Zone, Gongyi, Henan, China 450012
Website: www.huaxingcable.com
 E-mail: huaxing@huaxingcable.com
 Tel: 0086 371 8662 7929
 Fax: 0086 371 64108619

Triplex Secondary UD Cable 600V

Code Word	Phase Conductor			Neutral			Diameter (mils)		Weight Per 1000 feet (lbs.)	Allowable Ampacities+	
	Size (AWG)	Stranding	Insul. Thick. (mils)	Size (AWG)	Stranding	Insul. Thick. (mils)	Single Phase Cond.	Complete Cable		Direct Burial	In Ducts
TRIPLEXED WITH YELLOW EXTRUDED STRIPE NEUTRAL.											
Erskine	6	7	60	6	7	60	298	644	134	95	70
Vassar	4	7	60	4	7	60	345	745	191	125	90
Stephens	2	7	60	4	7	60	403	870	249	165	120
Ramapo	2	7	60	2	7	60	403	870	278	165	120
Brenau	1/0	9	80	2	7	60	512	1106	387	215	160
Bergen	1/0	9	80	1/0	9	80	512	1106	441	215	160
Converse	2/0	11	80	1	9	80	555	1199	478	245	180
Hunter	2/0	11	80	2/0	11	80	555	1199	535	245	180
Hollins	3/0	17	80	1/0	9	80	603	1302	581	280	205
Rockland	3/0	17	80	3/0	17	80	603	1302	651	280	205
Sweetbriar	4/0	18	80	2/0	11	80	658	1421	709	315	240
Monmouth	4/0	18	80	4/0	18	80	658	1421	796	315	240
Pratt	250	26	95	3/0	17	80	732	1581	853	345	265
Wesleyan	350	37	95	4/0	18	80	831	1795	1118	415	320
Holyoke	500	37	95	300	37	95	980	2117	1545	495	395
Rider	500	37	95	350	37	95	980	2117	1598	495	395

+Ampacity: 90°C conductor temperature, 20°C ambient, RHO 90, 100% load factor for three conductor triplex with neutral carrying only unbalanced load. Technical data for cable with solid black neutral is identical to yellow extruded stripe data except for "YES" suffix to code word. Also available in paralleled construction. For NEC Applications, use NEC Table 310.16 Ampacities.